


Light type Plastic conduit systems (320Nt)

SUPERSOL® PLUS ISR Junction box with plug in grommets



RAL 1023



Application Standard
EN 60670-22

Patents protected
1009810, EP2698792, 1010513



Properties



Box raw material	PO blend
Temperature range	-25°C to +60°C
Electrical characteristics	With electrical insulated characteristics
Resistance to flame propagating	Non flame propagating
Number of entries	7
Kind of entries	Plug in grommets
Ingress protection	IP 55
Number of base knock outs	4
Conduit alignment	Yes
Condensation opening	Yes
Flame retardant	650°C
Voltage	800V
Halogen free	No toxic gases in case of fire
Low acidity	No corrosive gases in case of fire
UV stability	Yes
Rodent repellent	Not attractive to rodents
Antistatic Technology	Yes
Antiscratch Technology	Yes

* Cover plate and plug in seals are made of PE

Watertight due to its elastic and directly mounted cover plate.

Junction boxes with grommets: These boxes are provided with stepped grommets for easy positioning of cables, without the use of additional fittings, after cutting at the pre-marked points.



Type	Part number	length mm	width mm	height mm		
Ø16/20	3036016	67	67	38	10	240
Ø20/16	3036020	82	82	43	10	160
Ø25/32	3036025	101	101	51	5	40